

LIDAR LR

HAND-HELD POLICE LASER



NEW
from
STALKER

Newly engineered from the ground up

- GREATER RANGE
- CONSISTENT TARGET TRACKING
- FASTER TARGET ACQUISITION
- UPDATED ELECTRONICS
- NEWLY DESIGNED OPTICS



The re-engineered Stalker LIDAR LR is the top choice for precision speed detection of closely bunched vehicles and is right at home in urban traffic settings.

Whether used by the mounted officer or dismounted patrol officer, the LIDAR LR allows pinpoint accuracy in settings that would be a challenge to other means of speed measurement.

New Forward-Swept Li-ion Handle

LIDAR LR's new Li-ion forward-swept handle facilitates a more natural grip with less tension on the wrist and better posture for the operator.



Newly Designed Optics: The Heart of the LR

The new 44mm lenses provide better target illumination, greater signal-to-noise ratio, and clearer return signal reception. All optical improvements add up to a typical distance of 4,000 feet.



Speed and Range in Heads-Up Display

Pioneered by Stalker's original LIDAR, the LR's Heads-Up Display (HUD) shows both speed and range information together and visible to the operator. This allows target distance confirmation without having to lower the device from eye level to look at the LCD.

STALKER[®] Radar | Lidar
The World Leader in Speed Measurement

1-800-GATELYS
www.gately.com

StalkerRadar.com

Gately

COMMUNICATION CO.

LIDAR LR

HAND HELD POLICE LASER

New Electronics Improve Processing

Internal circuit boards have been combined for speedier processing and easier service. The result is a 284:1 increase in processing power yielding an increase in time and resolution.

Dynamic Range Capabilities

The STALKER LIDAR LR now features an improved tracking algorithm, leading to smoother tracking, fewer dropouts, and a reduced sweep effect.

Single-Shot and Continuous Tracking Modes

The LIDAR LR can be set in Single-Shot mode where the trigger is pressed and the unit locks on a single speed reading. Or, the unit can be operated in tracking mode where the trigger is pressed and the unit takes continuous, real-time speed readings.

Doppler-Type Audio Tracking

Since most laser operators also operate radar, the LIDAR LR generates a continuous Doppler-type audio tone which correlates to the target speed. Just like the audio on a police radar, this audio is a substantial aid to understanding and building a target tracking history - providing a better evidentiary case for citations.



Specifications (LIDAR LR and LIDAR LR-EU)

Dimensions:	9.4" Height, 6.8" Length, 4.2" Width (23.9 cm Height, 17.3 cm Length, 10.7 cm Width)
Weight:	Including Battery Handle - 3.9 lbs (1.77 kg)
Housing:	Metal case with rubber end caps
Environmental:	-30° to +60° C, operating -40° to +85° C, non-operating
Humidity Protection:	+37° C, 90% Relative Humidity
Battery Life:	Typically 300 - 330 charge cycles
Battery Charge:	Li-ion battery: Approx. 2 - 3 shifts (6) AA Alkaline batteries: Approx. 2 shifts (6) AA Rechargeable batteries: Approx. 2 shifts
Type:	Handheld LIDAR offering Tracking mode, Single-Shot mode, and Time/Distance mode.
Acquisition Time:	Less than .4 second
Typical Range :	Typical range is 5 feet to > 4,000 feet (1.52 m to > 1,219 m)
Range Accuracy:	± .5 feet (.15 meter)
Speed Measure:	2 mph to 299 mph (2 km/h to 481 km/h, 2 knots to 344 knots)
Speed Accuracy:	± 1 mph (± 2 km/h, ± 1 knots)
Time/Dist. trigger mode:	Separate trigger depressions when target enters and exits speed zone.
Remote Trigger:	Remote trigger signal available through I/O Port.
Target Speed Tone:	Variable audio tone corresponding to target speed.
Target Return Tone:	No tone when beam is off target; tone repetition increases as beam moves into target and return signal quality increases.
Switching Output:	I/O Port signal for operation of external devices (e.g. a camera). Toggles when speed exceeds speed signal setting. (special order only)
Operating Wavelength:	905 ± 10 nm Peak @ 25° C
Eye Safety:	FDA/CDRH CLASS 1 Laser Device (Eyesafe) LR-EU: EN60825-1, Class 1M
Pulse Width:	< 30 nsec.
Beam Divergence:	< 3 mrad FWHM. 3 feet x 3 feet @1000 feet (.9 meters x .9 meters @ 304.8 meters)
Spanish LCD Available	

Features include

- Newly Designed Optics
- Updated Electronics
- New ergonomic, rechargeable battery handle provides better balance, which means less physical stress
- Integrated battery charger
- Improved latch-secured handle
- State-of-the-art Surface Mount Technology
- New 32-bit processor compared to the previous 8-bit processor
- New CPU's clock rate is 5X faster for faster target acquisition
- Standardized receiver board built to accommodate future enhancements
- Time Distance Converter (TDC) for improved time/distance measurements
- Doppler Audio Tracking

LIDAR LR-EU Approved

STALKER®

Radar | Lidar



Measurement



Authorized Dealer
Gately Communication Co.
Jill Gill, GSA Sales Rep
1-800-335-5431
Email: jgill@gately.com
GSA Contract GS-07F-8964D
Expires 7-31-2016

StalkerRadar.com



COMMUNICATION CO.

www.gately.com

501 Industry Drive, Hampton, VA 23661
Phone: 1-800-335-5431 / Fax: 757-825-5631

Jill Gill, GSA Representative
Direct Phone: 757-826-8216 x3035
Email: jgill@gately.com

STALKER Radar Lidar
The World Leader in Speed Measurement

ISO 9001 Certified Company

For

GSA Contract: GS-07F-8964D

Expires: 7-31-2016

Gately GSA Lidar LR Packages

Package A

Part #808-0010-00

LIDAR-LR Laser Instrument

One Rechargeable LI-ION Battery (Handle)**

AC Inline Charging Cable

Operator Manual

12 Month warranty

GSA PRICE: \$2,836.41

Package B

Part #808-0011-00

LIDAR-LR Laser Instrument

Two Rechargeable LI-ION Batteries (Handles)**

Battery (Handle) Charger Stand

Soft Padded Storage Bag

Operator manual

12 Month warranty

GSA PRICE: \$3,025.82

**May substitute handle for model that holds standard AA cell non-rechargeable batteries

Authorized Dealer

Gately Communication Co.

Jill Gill, GSA Sales Rep

1-800-335-5431

Email: jgill@gately.com

GSA Contract GS-07F-8964D

Expires 7-31-2016